

# S-1095 DIESEL TRANSLOADER



**SPECIFICATIONS**

## Measurement & Safety

### Systems

- TopTech Multiload II SMP Controller/or Accuload Legal for Trade
- Scully Intellitrol Grounding and Overfill Protection system
- Air eliminator c/w integral level control
- Automated pre-set control valve
- API Coupling and Artic Loading hoses
- Measurement Canada Certified Meter
- 

## Mechanical/Electrical

- Low temperature piping and components
- Piping designed and constructed to ASME B31.3
- Complete QC documentation
- Skidded module design allows for future permanent placement
- Approved by Professional Engineer
- Bidirectional Flow Design
- 480 Vac 3P 60 Amp Service
- 25hp Blackmer vane pump
- VFD Motor Control

## Features

- Gantry with hydraulic actuated loading platform and meets and exceed OH&S
- Safety top access loading hoop
- Highway transportable on DOT approve Tandem Trailer
- CSA C22 Canadian Electric Code API 505 & 541 Area Classification
- Transfer of Diesel between Rail Car and Truck at a rate of 1500L/min and 400 Gal/min
- BOL Ticket Printer
- Card Reader option
- 25' retractable mast lighting option
- On board generator option

[WWW.SKYEYE.CA](http://WWW.SKYEYE.CA)

Email:  
[Sales@Skyeye.ca](mailto:Sales@Skyeye.ca)